



Shell Corena S3 R 46

- Long Life
- Improved Efficiency

Premium Rotary Air Compressor Oil

Shell Corena S3 R is a premium quality air compressor oil designed to deliver high performance lubrication of rotary sliding vane and screw air compressors. It uses an advanced additive system to provide excellent protection and performance for compressors running with oil maintenance intervals of 4,000 hours and up to 6,000 hours under certain conditions

DESIGNED TO MEET CHALLENGES

Performance, Features & Benefits

- **Long oil life – Maintenance saving**

Shell Corena S3 R is capable of providing oil maintenance intervals of 4,000 hours (where allowed by manufacturers) even when operating at maximum discharge temperatures of up to 100°C. This may be extended to up to 6,000 hours under certain conditions.

It is formulated to help:

- Resist formation of carbon deposits in sliding vane slots in vane compressors
- Resist formation of deposits on rotating components in screw compressors
- Resist thermal breakdown and deposit formation to maintain excellent internal surface cleanliness particularly in oil/air separator and coalescer systems.
- The exact oil maintenance interval will depend on intake air quality, duty cycle and ambient conditions. For hot and humid type climates as found in the Asian and Pacific regions, the lower oil drain period of 4,000hrs is recommended (also consult OEM recommendations).
- **Outstanding wear protection**
With many years of successful application, Shell Corena S3 R helps provide effective protection of internal metal surfaces from corrosion and wear.
It contains an advanced ashless anti-wear system to help prolong the life of critical parts such as bearings and gears.

- **Maintaining system efficiency**

Air release and prevention of foaming are critical performance characteristics in a compressor oil, ensuring reliable start-up and continuous compressed air availability. Shell Corena S3 R is designed to provide rapid air release without excessive foaming to give trouble-free operation even under cycling conditions.

In addition, Shell Corena S3 R has excellent water separation properties to help ensure continuous efficient operation of the compressor even in the presence of water.

Main Applications



- **Rotary sliding vane and screw air compressors**

Shell Corena S3 R is suitable for use in oil-flooded/ oil injected single or two-stage rotary vane or screw air compressors.

Specifications, Approvals & Recommendations

- ISO 6743-3:2003(E) L-DAJ

For a full listing of equipment approvals and recommendations, please consult your local Shell Technical Helpdesk.

Compatibility & Miscibility

- **Seal Compatibility**

Shell Corena S3 R oils are compatible with seal materials specified for use with mineral oils.

Typical Physical Characteristics

| Properties | | | Method | Shell Corena S3 R 46 |
|---------------------|--------|--------------------|---------------|----------------------|
| ISO Viscosity Grade | | | ISO 3448 | 46 |
| Kinematic Viscosity | @40°C | mm ² /s | ASTM D445 | 46 |
| Kinematic Viscosity | @100°C | mm ² /s | ASTM D445 | 6.9 |
| Viscosity Index | | | ISO 2909 | 105 |
| Density | @15°C | kg/m ³ | ASTM D1298 | 868 |
| Flash Point (COC) | | °C | ASTM D92 | 230 |
| Air Release | | minutes | ASTM D3427 | 3 |
| RPVOT | | minutes | ASTM D2272 | 700 |
| FZG Test | | LS Fail | CEC-L-07-A-95 | 11 |
| Pour Point | | °C | ASTM D97 | -30 |
| Water Separability | @54°C | minutes | ASTM D1401 | 15 |

These characteristics are typical of current production. Whilst future production will conform to Shell's specification, variations in these characteristics may occur.

Health, Safety & Environment

• Health and Safety

Shell Corena S3 R is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Material Safety Data Sheet, which can be obtained from <http://www.epc.shell.com/>

• Protect the Environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.

Additional Information

• Advice

Advice on applications not covered here may be obtained from your Shell representative.

Viscosity - Temperature Diagram for Shell Corena S3 R

