Version 1.2

Revision Date 10.04.2017

Print Date 11.04.2017

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Product name	:	Shell Gadus S5 V100 2

Product code	: 001D8423
Product code	. 001D842

Manufacturer or supplier's details

Manufacturer/Supplier	:	Shell India Markets Private Limited (U23201TN2004PTC053147) 2nd Floor, Campus 4A RMZ Millenia Park 143 Dr. MGR Road, Perungudi CHENNAI 600096 India
Telephone	:	(+91) 04443450000
Telefax		(+91) 04443451516
Emergency telephone number	:	+91 22 6516 1058
Recommended use of the ch	nem	ical and restrictions on use
Recommended use	:	Automotive and industrial grease.

2. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature

: A lubricating grease containing polyolefins, synthetic esters and additives.

Hazardous components

3. HAZARDS IDENTIFICATION

Based on available data this substance / mixture does not meet the classification criteria.

Label elements

Safety data sheet available on request.

Hazard pictograms Signal word	:	No Hazard Symbol required : No signal word
Hazard statements		: PHYSICAL HAZARDS: Not classified as a physical hazard according to CLP criteria.

_

Version 1.2	Revision Date 10.04.2017	Print Date 11.04.2017
	HEALTH HAZARDS: Not classified as a health hazard unde ENVIRONMENTAL HAZARDS: Not classified as environmental hazar criteria.	
Precautionary statements	 Prevention: No precautionary phrases. Response: No precautionary phrases. Storage: No precautionary phrases. Disposal: No precautionary phrases. 	

Other hazards

Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis. Used grease may contain harmful impurities. High-pressure injection under the skin may cause serious damage including local necrosis. Not classified as flammable but will burn.

4. FIRST-AID MEASURES

General advice	Not expected to be a health hazard when used under no conditions.	rmal
If inhaled	No treatment necessary under normal conditions of use. If symptoms persist, obtain medical advice.	
In case of skin contact	 Remove contaminated clothing. Flush exposed area with water and follow by washing with soap if available. If persistent irritation occurs, obtain medical attention. 	Ì
	When using high pressure equipment, injection of produc under the skin can occur. If high pressure injuries occur, casualty should be sent immediately to a hospital. Do no for symptoms to develop. Obtain medical attention even in the absence of apparen wounds.	the t wait
In case of eye contact	 Flush eye with copious quantities of water. Remove contact lenses, if present and easy to do. Contining. If persistent irritation occurs, obtain medical attention. 	nue
If swallowed	In general no treatment is necessary unless large quantil are swallowed, however, get medical advice.	ties
Most important symptoms and effects, both acute and delayed	 Oil acne/folliculitis signs and symptoms may include form of black pustules and spots on the skin of exposed areas Ingestion may result in nausea, vomiting and/or diarrhoe 	6.

Version 1.2	Revision Date 10.04.2017	Print Date 11.04.2017
	Local necrosis is evidenced by de tissue damage a few hours follow	
Protection of first-aiders	: When administering first aid, ensuappropriate personal protective ec incident, injury and surroundings.	
Notes to physician	 Treat symptomatically. High pressure injection injuries reintervention and possibly steroid t 	
	damage and loss of function. Because entry wounds are small a seriousness of the underlying dan determine the extent of involveme anaesthetics or hot soaks should can contribute to swelling, vasosp surgical decompression, debriden foreign material should be perforn anaesthetics, and wide exploratio	nage, surgical exploration to ent may be necessary. Local be avoided because they asm and ischaemia. Prompt nent and evacuation of ned under general

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	:	Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.
Unsuitable extinguishing media	:	Do not use water in a jet.
Specific hazards during firefighting	:	Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide may be evolved if incomplete combustion occurs. Unidentified organic and inorganic compounds.
Specific extinguishing methods	:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Special protective equipment for firefighters	:	Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).

6. ACCIDENTAL RELEASE MEASURES

Personal precautions,	: Avoid contact with skin and eyes.

Version 1.2		Revision Date 10.04.2017	Print Date 11.04.2017
protective equipment and emergency procedures Environmental precautions	:	Use appropriate containment to avoid contamination. Prevent from spreading ditches or rivers by using sand, earth, barriers.	g or entering drains,
Methods and materials for containment and cleaning up	:	Prevent from spreading or entering int rivers by using sand, earth, or other a	
Additional advice	:	For guidance on selection of personal see Chapter 8 of this Safety Data She For guidance on disposal of spilled ma this Safety Data Sheet.	et.

7. HANDLING AND STORAGE

General Precautions :	Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.
Advice on safe handling :	Avoid prolonged or repeated contact with skin. Avoid inhaling vapour and/or mists. When handling product in drums, safety footwear should be worn and proper handling equipment should be used. Properly dispose of any contaminated rags or cleaning materials in order to prevent fires.
Avoidance of contact :	Strong oxidising agents.
Storage	
Other data :	Keep container tightly closed and in a cool, well-ventilated place. Use properly labeled and closable containers.
	Store at ambient temperature.
Packaging material :	Suitable material: For containers or container linings, use mild steel or high density polyethylene. Unsuitable material: PVC.
Container Advice :	Polyethylene containers should not be exposed to high temperatures because of possible risk of distortion.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Components with workplace control parameters

Version 1.2

Revision Date 10.04.2017

Biological occupational exposure limits

No biological limit allocated.

Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods http://www.cdc.gov/niosh/

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods http://www.osha.gov/

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances http://www.hse.gov.uk/

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA), Germany http://www.dguv.de/inhalt/index.jsp

L'Institut National de Recherche et de Securité, (INRS), France http://www.inrs.fr/accueil

Engineering measures :	 The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include: Adequate ventilation to control airborne concentrations.
	Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.
	General Information:
	Define procedures for safe handling and maintenance of controls.
	Educate and train workers in the hazards and control
	measures relevant to normal activities associated with this product.
	Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.
	Drain down system prior to equipment break-in or maintenance.
	Retain drain downs in sealed storage pending disposal or subsequent recycle.
	Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

Personal protective equipment

Protective measures

Personal protective equipment (PPE) should meet recommended national standards. Check with

ersion 1.2	Revision Date 10.04.2017	Print Date 11.04.2017
PPE suppliers.		
Respiratory protection	 No respiratory protection is ordinarily required under normal conditions of use. In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material. If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for th specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. Select a filter suitable for the combination of organic gases and vapours [Type A/Type P boiling point >65°C (149°F)]. 	
Hand protection Remarks	: Where hand contact with the pro- gloves approved to relevant stan US: F739) made from the followi suitable chemical protection. PV gloves Suitability and durability of usage, e.g. frequency and durati resistance of glove material, dex from glove suppliers. Contamina replaced. Personal hygiene is a care. Gloves must only be worn gloves, hands should be washed Application of a non-perfumed m	dards (e.g. Europe: EN374, ng materials may provide C, neoprene or nitrile rubber of a glove is dependent on on of contact, chemical terity. Always seek advice ted gloves should be key element of effective hand on clean hands. After using and dried thoroughly.
	For continuous contact we recombreakthrough time of more than a for > 480 minutes where suitable short-term/splash protection we recognize that suitable gloves of may not be available and in this time maybe acceptable so long a and replacement regimes are fol a good predictor of glove resistand dependent on the exact composible Glove thickness should be typicated by the glove make an and the glove make an and the glove make an and the stated by the should be typicated by the should be typicated by the glove make an and the should be typicated by the should by typicated by the should by typicated by ty	240 minutes with preference e gloves can be identified. For recommend the same, but fering this level of protection case a lower breakthrough as appropriate maintenance lowed. Glove thickness is not nce to a chemical as it is ition of the glove material. ally greater than 0.35 mm
Eye protection	: If material is handled such that it protective eyewear is recommen	
Skin and body protection	: Skin protection is not ordinarily rework clothes. It is good practice to wear chemi	
Thermal hazards	: Not applicable	

Environmental exposure controls

General advice	: Take appropriate measures to fulfill the requirements of	
----------------	------------------------------------------------------------	--

Version 1.2	Revision Date 10.04.2017	Print Date 11.04.2017
	relevant environmental protection contamination of the environment Chapter 6. If necessary, prevent u being discharged to waste water. V treated in a municipal or industrial before discharge to surface water. Local guidelines on emission limits must be observed for the discharg vapour.	by following advice given in indissolved material from Waste water should be waste water treatment plant

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	Semi-solid at ambient temperature.
Colour	:	light brown
Odour	:	Slight hydrocarbon
Odour Threshold	:	Data not available
рН	:	Not applicable
Drop point	:	260 °C / 500 °FMethod: IP 396
Initial boiling point and boiling range	:	Data not available
Flash point	:	Not applicable
Evaporation rate	:	Data not available
Flammability (solid, gas)	:	Data not available
Upper explosion limit	:	Typical 10 %(V)
Lower explosion limit	:	Typical 1 %(V)
Vapour pressure	:	< 0.5 Pa (20 °C / 68 °F) estimated value(s)
Relative vapour density	:	> 1estimated value(s)
Relative density	:	0.900 (15 °C / 59 °F)
Density	:	900 kg/m3 (15.0 °C / 59.0 °F) Method: Unspecified
Solubility(ies)		
Water solubility	:	negligible
Solubility in other solvents	:	Data not available
Partition coefficient: n- octanol/water	:	Pow: > 6(based on information on similar products)
Auto-ignition temperature	:	> 320 °C / 608 °F

Version 1.2	Revision Date 10.04.2017	Print Date 11.04.2017
Viscosity		
Viscosity, dynamic	: Data not available	
Viscosity, kinematic	: Not applicable	
Explosive properties	: Not classified	
Oxidizing properties	: Data not available	
Conductivity Decomposition temperature	This material is not expected to beData not available	e a static accumulator.

10. STABILITY AND REACTIVITY

Reactivity	: The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.
Chemical stability	: Stable.
Possibility of hazardous reactions	: Reacts with strong oxidising agents.
Conditions to avoid	: Extremes of temperature and direct sunlight.
Incompatible materials	: Strong oxidising agents.
Hazardous decomposition products	: Hazardous decomposition products are not expected to form during normal storage.

11. TOXICOLOGICAL INFORMATION

	Basis for assessment	:	Information given is based on data on the components and the toxicology of similar products.Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).
	Information on likely routes of exposure	:	Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.
Ac	ute toxicity		
	Product:		
	Acute oral toxicity	:	LD50 rat: > 5,000 mg/kg Remarks: Expected to be of low toxicity:
	Acute inhalation toxicity	:	Remarks: Not considered to be an inhalation hazard under normal conditions of use.

Version 1.2	Revision Date 10.04.2017	Print Date 11.04.2017
Acute dermal toxicity	: LD50 Rabbit: > 5,000 mg/kg Remarks: Expected to be of low toxicity	<i>I</i> .

Skin corrosion/irritation

Product:

Remarks: Expected to be slightly irritating., Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.

Serious eye damage/eye irritation

Product:

Remarks: Expected to be slightly irritating.

Respiratory or skin sensitisation

Product:

Remarks: Not expected to be a skin sensitiser.

Germ cell mutagenicity

Product:

Remarks: Not considered a mutagenic hazard.

Carcinogenicity

Product:

Remarks: Not expected to be carcinogenic.

Reproductive toxicity

Product:

Remarks: Not expected to impair fertility., Not expected to be a developmental toxicant.

STOT - single exposure

Product:

Remarks: Not expected to be a hazard.

STOT - repeated exposure

Product:

Version 1.2

Revision Date 10.04.2017

Print Date 11.04.2017

Remarks: Not expected to be a hazard.

Aspiration toxicity

Product:

Not considered an aspiration hazard.

Further information

Product:

Remarks: Used grease may contain harmful impurities that have accumulated during use. The concentration of such harmful impurities will depend on use and they may present risks to health and the environment on disposal., ALL used grease should be handled with caution and skin contact avoided as far as possible.

Remarks: High pressure injection of product into the skin may lead to local necrosis if the product is not surgically removed.

Remarks: Slightly irritating to respiratory system.

12. ECOLOGICAL INFORMATION

Basis for assessment	 Ecotoxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the ecotoxicology of similar products. Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).(LL/EL/IL50 expressed as the nominal amount of product required to prepare aqueous test extract).
Ecotoxicity	
Product:	
Toxicity to fish (Acute toxicity)	: Remarks: Expected to be practically non toxic: LL/EL/IL50 > 100 mg/l
Toxicity to crustacean (Acute toxicity)	: Remarks: Expected to be practically non toxic: LL/EL/IL50 > 100 mg/l
Toxicity to algae/aquatic plants (Acute toxicity)	: Remarks: Expected to be practically non toxic: LL/EL/IL50 > 100 mg/l
Toxicity to fish (Chronic	: Remarks: Data not available
toxicity) Toxicity to crustacean (Chronic toxicity)	: Remarks: Data not available

Version 1.2	Revision Date 10.04.2017	Print Date 11.04.2017
Toxicity to microorganisms (Acute toxicity)	: Remarks: Data not available	
Persistence and degradability		
Product:		
Biodegradability	Remarks: Expected to be not readily b constituents are expected to be inhere contains components that may persist	ntly biodegradable, but
Bioaccumulative potential		
Product:		
Bioaccumulation	: Remarks: Contains components with the bioaccumulate.	ne potential to
Partition coefficient: n- octanol/water	: Pow: > 6Remarks: (based on informati	on on similar products)
Mobility in soil		
Product:		
Mobility	 Remarks: Semi-solid under most envir it enters soil, it will adsorb to soil partic mobile. Remarks: Floats on water. 	
Other adverse effects		
no data available <u>Product:</u>		
Additional ecological information	 Product is a mixture of non-volatile correspected to be released to air in any s Not expected to have ozone depletion photochemical ozone creation potentia potential. Poorly soluble mixture., May cause phorganisms. 	ignificant quantities., potential, Il or global warming

13. DISPOSAL CONSIDERATIONS

Disposal methods	
Waste from residues	 Recover or recycle if possible. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations. Do not dispose into the environment, in drains or in water courses
	Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment. Waste, spills or used product is dangerous waste.

Version 1.2	Revision Date 10.04.2017	Print Date 11.04.2017
Contaminated packaging	: Dispose in accordance with prevailing regulations, preferably to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand. Disposal should be in accordance with applicable regional, national, and local laws and regulations.	
Local legislation Remarks	: Disposal should be in accordance national, and local laws and regula	

14. TRANSPORT INFORMATION

International Regulations

ADR

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Pollution category	: Not applicable
Ship type	: Not applicable
Product name	: Not applicable
Special precautions	: Not applicable

Special precautions for user

Remarks

: Special Precautions: Refer to Chapter 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.

Additional Information : MARPOL Annex 1 rules apply for bulk shipments by sea.

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

The Manufacture, Storage and Import of Hazardous Chemicals Rules 1989 (amended version issued 2000). The Factories Act, 1948, The Second Schedule: Permissible levels of certain chemical substances in work environment, as amended through 1987. India Central motor Vehicles (Amendment) Rules 1993.

Other international regulations

The components of this product are reported in the following inventories:

•	•	•	U
EINECS	:	All components	listed or polymer exempt.
TSCA	:	All components	listed.

Version 1.2		Revision Date 10.04.2017	Print Date 11.04.2017
16. OTHER INFORMATION			
Abbreviations and Acronyms	:	: The standard abbreviations and acronyms used in this document can be looked up in reference literature (e.g. scientific dictionaries) and/or websites.	
SDS Regulation	:	Regulation 1907/2006/EC	
Further information Other information	:	A vertical bar () in the left margin indic from the previous version.	ates an amendment

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.